

NEW**SARA® Threading inserts, full profile 60****1099**

• Full profile 60

Full profile, ISO external right-hand, groundISO **K M N P S**




ISO designation	l mm	Pitch mm	☐	SPU20T art.no.	€
16 ER 0.5 ISO	16	0.5	2	342803 0142	11,20
16 ER 0.75 ISO	16	0.75	2	342803 0242	11,20
16 ER 0.8 ISO	16	0.8	2	342803 0342	11,20
16 ER 1.0 ISO	16	1.0	2	342803 0442	11,20
16 ER 1.25 ISO	16	1.25	2	342803 0542	11,20
16 ER 1.5 ISO	16	1.5	2	342803 0642	11,20
16 ER 1.75 ISO	16	1.75	2	342803 0742	11,20
16 ER 2.0 ISO	16	2.0	2	342803 0842	11,20
16 ER 2.5 ISO	16	2.5	2	342803 0942	11,20
16 ER 3.0 ISO	16	3.0	2	342803 1042	11,20

3165

Full profile, ISO internal right-hand, ground on inner rightISO **K M N P S**

ISO designation	l mm	Pitch mm	☐	SPU20T art.no.	€
16 IR 1.0 ISO	16	1.0	2	343003 0142	11,20
16 IR 1.25 ISO	16	1.25	2	343003 0242	11,20
16 IR 1.5 ISO	16	1.5	2	343003 0342	11,20
16 IR 1.75 ISO	16	1.75	2	343003 0442	11,20
16 IR 2.0 ISO	16	2.0	2	343003 0542	11,20
16 IR 2.5 ISO	16	2.5	2	343003 0642	11,20
16 IR 3.0 ISO	16	3.0	2	343003 0742	11,20

3165

**NEW****SARA® Threading inserts, full profile 55****1099**

• Full profile 55

Full profile, 55° external right-hand, groundISO **K M N P S**

ISO designation	l mm	Pitch TPI	☐	SPU20T art.no.	€
16 ER 11W	16	11	2	344403 0342	11,20
16 ER 14W	16	14	2	344403 0242	11,20
16 ER 19W	16	19	2	344403 0142	11,20

3165

Full profile, 55° internal right-hand, groundISO **K M N P S**

ISO designation	l mm	Pitch TPI	☐	SPU20T art.no.	€
16 IR 11W	16	11	2	344604 0342	11,20
16 IR 14W	16	14	2	344604 0242	11,20
16 IR 19W	16	19	2	344604 0142	11,20

3165

